

WeatherTuff®

Building Surface Solutions



Ready To Use For
Watertight Plastering Two
Part Waterproofing System

Diamond Shield

An ultimate solution to all water leakages in the masonry work. A two component ready to use Diamond shield is the most effective long term solution for Roofs, Walls, Storage tanks, Water Canals and Bridges, to protect them from chlorination and oxidation.

Available Sizes

1Kgs, 5Kgs, 25Kgs, 50Kgs.

Advantages

- Cost effective & ready to use two components.
- Can be used for protection of steel structure from chlorination and oxidation.
- Simple application by brush, mason apparatus or plastering applicators.
- Environment friendly.

Application

- It can be applied on Roofs, Walls, Terraces, Parapet Walls, sloping roof & side walls of buildings with thick layer coating for waterproofing. It covers 4 to 6 Sq. Ft. in 2 coats.
- It gives excellent results when applied in the sunk portion of the bathrooms, toilets and swimming pools.
- Can be applied as an under layer for terrace tiles work and also as a filler to tile joints.
- For Coating structured steel of beams and columns.

Note:- For all sun exposed Diamond Shield coatings. It is essential to over coat with Sealer coat or Insultec



Diamond Shield

Manufactured & Marketed By :

Chitra Insultec Pvt. Ltd.

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura,
Ahmedabad-380009. (Gujarat) INDIA.

Phone : +91-79-2656 2100 | Telefax : +91-79-2656 4777

Email : info@weathertuff.com | Web : www.weathertuff.com

TOLL FREE NO. : 18001239010