

# WeatherTuff®

Building Surface Solutions

# GLAZE COAT

Acrylic Base Water repellent clear coat  
(For exterior & interior Wall protection)

## Advantages:

- For Glaze or Shining finish of any exterior or interior coated surface and to reduce dust collection, apply GLAZE COAT.
- It seals the porosity of cement plaster, stones & makes it moderate water repellent.
- It is transparent and moderately U. V. Resistant.
- Can be also applied over stone to get better protection against water, oil, algae & fungus.
- We recommend to apply GLAZE COAT as top coat to any surface coatings for better heat re-radiation and avoid dust collection.

## How To Apply:

- Clean the surface thoroughly & make it free from loose dust & oil.
- Wash the surface with water.
- Apply the first coat of GLAZE COAT by brush or spray.
- Let the first coat dry for 2-3 hours. Then apply another coat of GLAZE COAT.
- Make sure no dust layer is formed between surface of each coat.
- Two coats are necessary for better results.

## Coverage:

On smooth surface, 1 litre. GLAZE COAT covers 70 to 80 sq. ft. in 2 coats.

**Available in :** 1kgs, 5kgs, 20kgs & 50kgs.

## For Use On:

- To extend the weathering properties of Acrylic.
- Exterior surface of Storage Tank.
- Water Tank.
- Pipelines
- Bridges
- Commercial Building
- Can be apply on any coloured coat.
- Acceptable for use in high performance architectural application.



**Manufactured & Marketed By :**  
**Chitra Insultec Pvt. Ltd.**

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura, Ahmedabad-380009. (Gujarat) INDIA.

Phone : +91-79-2656 2100 | Telefax : +91-79-2656 4777

Email : [info@weathertuff.com](mailto:info@weathertuff.com) | Web : [www.weathertuff.com](http://www.weathertuff.com)

TOLL FREE NO. : 18001239010