

WeatherTuff®

Building Surface Solutions

SEALOXY PRIMER

For all Cementitious Surfaces

Acrylic, Waterbased, Waterproof Undercoat

Sealoxo Primer's Special Features

Sealoxo Primer gives 70 to 80 sq.ft coverage per Ltr on smooth surfaces.

Sealoxo white primer is 100% waterproofing undercoat. It gives better adhesion and longer life.

Sealoxo primer can be used as an undercoat for all paint.

Qualities

- Acrylic
- Water based
- Waterproof
- Under coat

Uses



Interior



Exterior



Terrace



Ceiling or Slab



R.C.C Structure




About Sealoxo Primer

Sealoxo Primer is an effective undercoat for indoor walls against minor moisture problems and for higher coverage of the paint. It is a thin coat which is flexible and stable. Sealoxo Primer is the first coat which is to be applied on a dry plastered wall. It fills the porosity in the plaster and makes it water resistant. To reduce overall painting cost, Sealoxo Primer is the best under coat.

Advantages

- Weathertuff Sealoxo Primer, an effective undercoat helps your indoor walls against minor moisture problems and keeps paint undamaged.
- It also helps preventing moisture penetration, when applied on outerwalls. DRY Sealoxo Primer film is thin, flexible, stable and white.
- When applied on dry plastered walls, it fills porosity of the plaster and make it water resistant.
- Flexible film of SEALOXY provides protection against expansion & contraction caused by variations of heat & cold in the atmosphere.
- Hence, the colour applied on its coating does not crack or chip.
- All water base colours can be applied on Sealoxo Primer.

Method of Application:



Step1

Dilute Sealoxo with water up to 15% to 20%.



Step2

Clean the surface



Step3

Apply one coat Sealoxo Primer by Brush or Roller.



Step4

Allow the surface to be cured for 3-4hrs before applying any other paint.

Manufactured & Marketed By :
Chitra Insultec Pvt. Ltd.

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura,
Ahmedabad-380009. (Gujarat) INDIA.

Phone : +91-79-2656 2100 | Telefax : +91-79-2656 4777

Email : info@weathertuff.com | Web : www.weathertuff.com

TOLL FREE NO. : 18001239010