

Description: TUFFSIL is a very economical, water soluble of active silicone designed to impart water repellence of masonry surface. It reduces masonry maintenance cost with long term improved resistance to tropical weather. After application of TUFFSIL, water evaporates & it reacts with moisture & carbondioxide in the air to form an insoluble, invisible repellent Silicone film within 24 hrs. It

Advantages: TUFFSIL treatment is effective on all types of masonry having open bricks Asb Sheet, Teracota & Mangalore Tiles, Sand stone, Plastered surface. It is microporous and allows breathing,

is resistance to UV Rays and weather.

- TUFFSIL keeps water on the run by forming an invisible Silicone Surface on the masonry wall. Collection of dust on the wall can be easily washed off.
- TUFFSIL is ready to use by brush or spray directly on surface.
- TUFFSIL Preserves original colour or texture of treated surface.



Weather Tuff

(SINGLE COAT TREATMENT)



• TUFFSIL does not clog the pores of surface, so allows surface to breath.

Direction of Uses: Surface should be free from Oil, Grease, Loose Particles, Algae & Fungus. All joints & cracks must be sealed properly, We suggest using modified mortar (Like - Weathertuff's Diamond shield) for greater bonding. Apply single coat ready to use TUFFSIL on the surface. It can be applied by brush or spray. After application of TUFFSIL, the treated surface should be allowed to dry for minimum 24hrs. to develop maximum water repellency.

Do not apply second coat.

Properties:

Colour : Clear liquid.

Sp. Gravity: 0.98

Coverage : 30 to 40 sq. Ft. per kg

depending on porosity of

substrate.

Self Life : 6 months in sealed tin.
Packing : 1 liter, 5 liter & 20 ltr.

Manufactured & Marketed By : Chitra Insultec Pvt. Ltd.

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura, Ahmedabad-380009. (Gujarat) INDIA.

Phone : +91-79-2656 2100 | Telefax : +91-79-2656 4777 | Email : info@weathertuff.com | Web : www.weathertuff.com

TOLL FREE NO.: 18001239010

TUFFSIL

Silicone water repellent for masonry