

ISO 9001: 2015





## EPOXY TILE GROUT

3 - Part High Strength Tiles Joint Filler



#### ISO 9001: 2015

- Area of Application: Toilets, Swimming Pools, Malls, Hotels, Restaurants, Theaters, Hospitals
- Surface Preparation: Joints should be free from oil, dust free or any contamination. Space should be proper dry & clean.
- Mixing of all Packing: Mix part 1 & Part 2 in a clean dry vessel and stir well properly. Now add powder part to this mixture in proper way according to your need.
  - It should not be in lump form consistency should be such that you can fill the joint very smoothly and easily.
- Application: Press the Epoxy Tilegrout Firmly in the joints and make sure that joints are fully
- filled. Clear the extra grout from joints and surface within 15 20 to minuets. Use dampen sponge with water to clear the surface in circular motion. For sparkle glossy look, use glitter gold/silver.

Advantages: 1. Higher in Strength

- 3. Resistant to acid, Chemicals
  - 5. Non Toxic
  - 7. Stain Free

- 2. Crack Free, Highly durable
- 4. Algae & fungus free6. Easy to maintain & clean
- 8. Long Lasting

**Note:** • Grout Shades are approximate guides only. • Verity actual appearance and compatibility with a test area before installation commences. • Actule shades and texture will depend on job site condition. • There may be a shade variation in different batches. It is advices to mix grout from different batches to get uniform colour.

• Quantities shown are approximate and are given for estimating purpose only. • Actual job site coverage's may vary. •It is always good practice when calculating coverage to allow for 10 to 15% additional material for wastage & spillage.

#### • Net Wt. in Kg.:

	<b>/</b>	
Part I	Hardner	120 Gms.
Part II	Base	170 Gms.
Part III	Filler	710 Gms.

N.B.: Gloves, Sponge, Metal Piece is included.

Best Before 18 months from the date of manufacturing.

# Net Weight : Batch No. : Date of Mfg : MRP : (Incl. of all taxes)

### Manufactured & Marketed By: CHITRA INSULTEC PVT. LTD.

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura, Ahmedabad-380009. (Gujarat) INDIA.

Phone: +91-79-2656 2100 | Telefax: +91-79-2656 4777 | Email: info@weathertuff.com | Web: www.weathertuff.com

**TOLL FREE NO.: 18001239010**