



Tuff Coat

Solvent base Ultra Premium Clear Protective Coat

MSDS :

Tuff Coat is solvent based single component, ultra premium protective coat. It adds to Waterproofing, Rust Resistance, Mild Termite Resistance to Wood and for total weather proofing over coat, on any paint coated surfaces.

Scratch resistant and shining for a long long time. It protects from oxidation of steel.

Tuff Coat is slow drying. It's drying time is approximately 4/5 hours. Hence necessary precautions should be taken.

Warning :

1. It has strong adhesive property among many other. Hence use it with utmost care.
2. Use hand gloves. Clean brush with mineral Turpentine after use. If contacted by skin clean with hot water or mild solvent.
3. Protect eyes by wearing eyeglass during application. If splashed in eyes clean with plenty of water immediately and consult physician if required.

Tuff Coat

Solvent base Ultra Premium Clear Protective Coat

Advantage :

Waterproofing & Rising dampness of construction surface. Rust resistance & long term protection of steel surface. Very hard & smooth surface coat for repellence of water, soil, dust & rust.

Tuff Coat is the final coat On Wood, MS Structure, Concrete or final painted surface will give total protection from all weather. It may also be over coated, with any desired texture. As it is slightly yellowish, do not apply on white coat. Excellent results are found to stop rising dampness on walls.

Application Method :

Prepare surface for application as for any other paint. Make surface clean and free from any dust, oil & grease, dry without any loose flakes. Use sand paper or Emery paper and remove loose residuals.

Clean such prepared surface by wet cloth so that surface is ready for application when completely dry.

Apply 1st coat of "**Tuff Coat**" on such prepared surface. Apply on two way cross brushing.

Apply 2nd coat after 3/4 hours. If you want to over coat with any other texture coat, sprinkle dry silica to make better bond.

Make sure no dust or other particle is getting stucked on surface while it is drying.

Check the surface after 4/5 hours of drying time.

Get the ultimate protection with "**Tuff Coat**" primer.

Available Size :

1 Kg., 5 Kg., 26 Kg. & 50 Kg.

Manufactured & Marketed By : Chitra Insultec Pvt. Ltd.